





# SCHUKO socket outlet 45° Berker S.1/B.3/B.7, polar white matt

Technical features

AICHILECTULE	Arc	hite	cture
--------------	-----	------	-------

Design	according to DIN 49440
Fixing mode	flush-mounting

## Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### **Electric current**

Rated current	16 A
---------------	------

# Cover, door

Cover	Central cover plate
-------	---------------------

## Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

### Dimensions

Insertion depth	32 mm
-----------------	-------

# Installation, mounting

Installation mode	with spreader claws
- for diagonal insertion	

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

## Safety

IK protection code against mecanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	

# Identification

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7



## Instructions

Information text Specially suited for combining several socket outlets if right angle plugs are used.