



41108913



**SCHUKO socket outlet with control LED and "SV" imprint with labelling field, enhanced contact protection, Screw-in lift terminals, Berker S.1/B.3/B.7, green glossy**

#### Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting
Technical version	Imprint "SV"

#### Connectivity

Type of USB port	other
------------------	-------

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Design lines special colours	green
Colour	green
Colour	green
RAL colour	RAL 6029 - Mint green
Material	duroplastic
Surface appearance	glossy

#### Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to VDE 0620-1:2021-02
- with screw-in lift terminals	

#### Use

Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 2 - Sales	enhanced contact protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

### Standards

Execution SV, ZSV	according to VDE 0100-710
-------------------	---------------------------

### Safety

Protection index IP	IP20
---------------------	------

Enhanced contact protection	according to IEC 60884-1
-----------------------------	--------------------------

Enhanced contact protection	according to VDE 0620-1:2021-02
-----------------------------	---------------------------------

- Enhanced contact protection	
-------------------------------	--

### Identification

Main design line	Berker S.1/B.3/B.7
------------------	--------------------

Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7
--------------------------	------------------------------------

### Instructions

Information text	Labelling field height arranged for P-touch strips 6 mm., Insert colour-coded.
------------------	--