



41101914



SCHUKO socket outlet with control LED and "ZSV" imprint with labelling field, enhanced contact protection, Screw-in lift terminals, Berker S.1/B.3/B.7, orange matt

Technical features

Architecture

Design	according to DIN 49440
Technical version	Imprint "ZSV"

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- Central cover plate

Materials

RAL colour	RAL 2003 - Pastel orange
Design lines special colours	orange
Colour	orange
Colour	orange
Material	thermoplastic
Surface appearance	matt

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

- with spreader claws

Connection

Connection terminals	according to VDE 0620-1
- with screw-in lift terminals	

Use

- with labelling field
- enhanced contact protection
- Screw-in lift terminals

Standards

Execution SV, ZSV	according to VDE 0100-710
-------------------	---------------------------

Safety

Protection index IP	IP20
IK protection code against mechanical impacts	05
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1
- Enhanced contact protection	

Identification

Main design line

Berker S.1/B.3/B.7

Instructions

- Labelling field height arranged for P-touch strips 6 mm.
 - Insert colour-coded.
-