



41101909



SCHUKO socket outlet with control LED with labelling field, enhanced contact protection, with screw-in lift terminals, Berker S.1/B.3/B.7, polar white matt

Technical features

Architecture

| | |
|-------------|------------------------|
| Design | according to DIN 49440 |
| Fixing mode | flush-mounting |

Connectivity

| | |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

Materials

| | |
|-----------------------|-----------------------|
| Colour of design line | polar white |
| Colour | polarwhite |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | thermoplastic |
| Surface appearance | matt |

Dimensions

| | |
|---|-------|
| Insertion depth | 32 mm |
| Installation depth, flush-mounted boxes | 31 mm |

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|--------------------------------|---------------------------------|
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with screw-in lift terminals | |

Use

| | |
|--|------------------------------|
| Differentiation characteristic 1 - Sales | with labelling field |
| Differentiation characteristic 2 - Sales | enhanced contact protection |
| Differentiation characteristic 3 - Sales | with screw-in lift terminals |

Safety

| | |
|-------------------------------|---------------------------------|
| Protection index IP | IP20 |
| Enhanced contact protection | according to IEC 60884-1 |
| Enhanced contact protection | according to VDE 0620-1:2021-02 |
| - Enhanced contact protection | |

Identification

| | |
|--------------------------|------------------------------------|
| Main design line | Berker S.1/B.3/B.7 |
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B.7 |

Instructions

| | |
|------------------|--|
| Information text | Labelling field height arranged for P-touch strips 6 mm. |
|------------------|--|
