



47549949

Double SCHUKO socket outlet with cover plate Berker S.1, anthracite matt

Technical features

Architecture

| | |
|-------------|------------------------|
| Design | according to DIN 49440 |
| Fixing mode | flush-mounting |

Connectivity

| | |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------|------------------|
| Cover | Full cover plate |
|-------|------------------|

Materials

| | |
|-----------------------|--------------------------|
| Colour of design line | anthracite |
| Colour | anthracite charcoal grey |
| RAL colour | RAL 7021 - Black grey |
| Material | thermoplastic |
| Surface appearance | matt |

Dimensions

| | |
|---|-------|
| Installation depth, flush-mounted boxes | 31 mm |
|---|-------|

Installation, mounting

| | |
|--------------------------------------|--------------------------|
| For installation in 1gang wall boxes | according to DIN 49073-1 |
|--------------------------------------|--------------------------|

Connection

| | |
|--------------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with plug-in terminals | |

Safety

| | |
|---|------|
| IK protection code against mechanical impacts | 05 |
| Protection index IP | IP20 |
| - without enhanced contact protection | |

Identification

| | |
|------------------|------------|
| Main design line | Berker S.1 |
|------------------|------------|