



41088982



**SCHUKO socket outlet with overvoltage protection with labelling field, Screw terminals, Berker S.1/B.3/B.7, white glossy**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting

**Controls and indicators**

- with acoustic fault signal

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Voltage**

Overvoltage protection	according to EN 61643 and VDE 0675-6-11
------------------------	---

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour of design line	white
Colour	white
Colour	white
RAL colour	RAL 1013 - Oyster white
Material	thermoplastic
Surface appearance	glossy

**Dimensions**

Insertion depth	32 mm
-----------------	-------

**Installation, mounting**

Installation mode	with spreader claws
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

**Equipment**

- with indicator LED for On/Error

---

**Use**

---

Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 3 - Sales	Screw terminals

---

**Safety**

---

IK protection code against mechanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	

---

**Identification**

---

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7

---

**Instructions**

---

Information text	Labelling field height arranged for P-touch strips 6 mm.
------------------	--

---