



3036



## Change-over switch Light control

### Technical features

#### Architecture

Type of control unit	single rocker
Fixing mode	flush-mounting

#### Functions

Switching angle	3,5 °
-----------------	-------

#### Configuration

- Off/change-over

#### Controls and indicators

- No

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

#### Electric current

Switching current	10 AX (100 W Self Ballasted Lamp (SBL))
-------------------	---

#### Materials

Material	Plastic/metal
Surface appearance	mat

#### Dimensions

Depth	42 mm
Insertion depth	31 mm
Height	71 mm
Width	71 mm

#### Installation, mounting

Installation mode	with spreader claws, for screw fastening
-------------------	--

#### Connection

Connection terminals	according to IEC 60669-1
Connection terminals	according to VDE 0632-1
Type of connection	Quickconnect
- with plug-in terminals	

#### Equipment

- for lighting and monitoring circuit

#### Safety

Protection index IP	IP20
---------------------	------

**Identification**

---

Application, usage	HVAC control, Light control
Appliance switch type	No
Main design line	Light control

---

**Instructions**

---

Information text	spreader claws, insulated to the supporting ring, self-resetting
------------------	--

---

- A control change-over switch is shown here as an example. With 2-pole and 3-pole control on/off switches, other rocker switches and neon lamp units are required.
-