


294810



## Time relay insert Light control

### Technical features

### Controls and indicators

- is switched off when actuated in the switched-on state

### Main electrical features

Nominal voltage	240 V
Frequency	50/60 Hz

### Electric current

Rated current	6 A
---------------	-----

### Fuse

Fuse	short-circuit and overload proof (fine-wire fuse), with spare fuse
------	---

### Power

Conventional transformers	1000 VA
Electronic transformers	1500 W

### Measurement

Extension unit input	with extension unit input for push-button (NO contact)
----------------------	--

### Materials

Colour	not applicable
Material	Plastic/metal

### Dimensions

Insertion depth	32,5 mm
Axis dimension Ø	4 mm

### Lighting control

- uncompensated	500 VA
-----------------	--------

### Fluorescent bulbs control

Fluorescent lamps in duo circuit	1000 VA
Fluorescent lamps parallel compensated	150 VA

### LED control

LED	with red control LED
-----	----------------------

### Incandescent bulbs control

230 V incandescent lamps	1500 W
230 V halogen lamps	300 W

---

**Installation, mounting**

---

Installation mode	with spreader claws
-------------------	---------------------

---

**Settings**

---

Delay time, adjustable	≈ 1 mn...1 h
------------------------	--------------

---

**Equipment**

- 
- very low noise
  - electronic timer with on/off pressure switch
- 

**Identification**

---

Application, usage	Light control
Main design line	Light control

---