product sheet 28199939





 $\begin{array}{c} & & & \\ & & & \\ & & & \\ & & & \\ & & & \\$

Rotary dimmer with cover plate Setting knob, with sof	ft-lock, Berker S.1, aluminium, matt, lacquered
Technical features	
Functions	
- bulb-preserving soft startup	
Main electrical features	
Nominal voltage	230 V
Frequency	50 Hz
Voltage	
Operating voltage	230 V AC
Fuse	
Fuse	short-circuit and overload proof (fine-wire fuse)
Power	
Loss power at full load	≈ 4 W
Materials	
Colour of design line	aluminium
Colour	aluminium
Material / workmanship	lacquered
Material	thermoplastic
Dimensions	
Axis dimension Ø	4 mm
Incandescent bulbs control	
230 V incandescent lamps and halogen lamps	60400 W
Installation, mounting	
Installation mode	with spreader claws
Connection	
Type of load	Resistive load
- with screw terminals	
Equipment	
phase cut-onwith rotary on/off switch	
Use	
Differentiation characteristic 2 - Sales	Setting knob
Differentiation characteristic 3 - Sales	with soft-lock
Use conditions	
Operating temperature	525 °C
- For and conference	520 0



Identification

Application, usage	Light control
Main design line	Berker S.1
Secondary design line(s)	House electronics