



16409906



## Relay switch with centre plate for hotel card Berker S.1/B.3/B.7, anthracite, matt

### Technical features

#### Architecture

Fixing mode flush-mounting

#### Configuration

- 1pole

#### Main electrical features

Nominal voltage 230 V

Rated voltage 230 V AC

Frequency 50/60 Hz

#### Electric current

Inductive load at  $\cos \varphi = 0.6$  max. 6 A

Switching current 10 A /230 V AC1

#### Power

Conventional transformers 1500 VA

Electronic transformers 1500 W

Power consumption < 0.2 W

#### Materials

Colour of design line anthracite

Colour anthracite

Colour anthracite charcoal grey

RAL colour RAL 7021 - Black grey

Material Plastic/metal

Surface appearance matt

#### Dimensions

Depth 57,3 mm

Insertion depth 32 mm

Card width max. 55 mm

Card thickness 0,8...1,2 mm

Height 71 mm

Width 71 mm

#### Fluorescent bulbs control

Compact fluorescent lamps 500 W

Fluorescent lamps in duo circuit 1500 W

#### LED control

LED illuminated with blue LED if hotel card is not inserted

---

**Incandescent bulbs control**

---

230 V incandescent lamps and halogen lamps 1500 W

---

**Installation, mounting**

---

Installation mode with spreader claws

---

**Connection**

---

Screw terminals (max.) 2 x 2,5 mm<sup>2</sup>

---

- with screw-in lift terminals

---

**Settings**

---

Delay time incrementally adjustable 0, 15, 30, 60 s

---

- with potentiometer for incremental adjustment of delay time

---

**Equipment**

---

- for illumination
  - with potential-free contact
- 

**Safety**

---

Protection index IP IP20

---

**Use conditions**

---

Operating temperature -5...50 °C

---

Storage/transport temperature -25...70 °C (storage at > 45°C reduces the service life)

---

**Identification**

---

Application, usage Light control

---

Main design line Berker S.1/B.3/B.7

---

Secondary design line(s) Berker S.1, Berker B.3, Berker B.7

---