



28850001



## Ceiling loudspeaker Ø 140 mm Communication technology, white

### Technical features

#### Frequency

Frequency response (-3 dB) 170...22000 Hz

#### Power

Nominal/music power handling 6/8 W

#### Resistance

Impedance 8 Ω

#### Detection

- at 1 kHz 180 °

- at 4 kHz 130 °

- at 8 kHz 80 °

#### Materials

Colour independent of design lines white

Material Mixed materials

#### Dimensions

Insertion depth 62 mm

Installation opening Ø 116 mm

Recommended installation height 2,4...4 m

Installation wall thickness 30 mm

Loudspeaker chassis Ø 87 mm

#### Installation, mounting

Installation mode with spring mechanism for ceiling installation

#### Connection

Conductor cross-section (flexible) max. 2,5 mm<sup>2</sup>

- with plug-in terminals

#### Cable

- with strain relief

#### Equipment

Sound pressure level 1 W/1 m 87 dB

Sound pressure level at rated power 95 dB

#### Safety

- with membrane impregnated against humidity

---

**Identification**

---

Application, usage	Communication technology
Main design line	Communication technology

---

**Instructions**

---

Information text	Suitable installation housings available from Kaiser and Spelsberg.
------------------	------------------------------------------------------------------------

---