



459410



## Aerial socket 4hole single box DC-permeable, Communication technology

### Technical features

### Functions

- Suitable for HDTV

### Connectivity

- remote supply via F-sockets
- with 2 independent SAT outputs (F-sleeves) and 2 IEC outputs (male/female)
- for terrestrial reception
- for digital and analogue transmission

### Voltage

- DC voltage conducting

### Frequency

Broadband technology 5...2400 MHz

### Resistance

Wave impedence 75 Ω

### Attenuation

Tap loss at 2150 MHz 2 dB

Tap loss at 860 MHz 2 dB

### Installation, mounting

- for community and broadband cable systems
- for single and distributor SAT systems
- for multi-switch systems

### Connection

Connection for simultaneous connection of radio and TV receiver as well as 2 independent SAT receivers

- with screw terminals

### Settings

- also to add SAT programmes in broadband cable systems

### Equipment

- external eyelets on the supporting ring can be broken off for round designs

### Use

Differentiation characteristic 3 - Sales DC-permeable

### Standards

General standards EN 50083-2 and EN 60728-4

---

**Safety**

---

Protective screen	(VHF/UHF) according to EN 50083-2, Class B, (SAT) according to EN 50083-2, Class A
Protection index IP	IP20

---

**Use conditions**

---

Operating temperature	-25...55 °C
-----------------------	-------------

---

**Identification**

---

Application, usage	Communication technology
Main design line	Communication technology

---