







SCHUKO socket outlet 45° Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered

Technical features

Arc	hite	cti	ıre

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

anthracite	Colour of design line
anthracite	Colour
anthracite charcoal grey	Colour
RAL 7021 - Black grey	RAL colour
lacquered	Material / workmanship
duroplastic	Material
velvety	Surface appearance

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	with spreader claws
- for diagonal insertion	

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	



Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9
Instructions	
Information text	Specially suited for combining several socket outlets if right angle plugs are used.