



41496084



**SCHUKO socket outlet with labelling field, enhanced contact protection, Screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9**

Technical features

### Architecture

|             |                        |
|-------------|------------------------|
| Design      | according to DIN 49440 |
| Fixing mode | flush-mounting         |

### Connectivity

|                  |       |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

### Electric current

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

### Cover, door

|       |                     |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

### Materials

|                        |                            |
|------------------------|----------------------------|
| Colour of design line  | aluminium                  |
| Colour                 | aluminium                  |
| Colour                 | aluminium optics           |
| RAL colour             | RAL 9006 - White aluminium |
| Material / workmanship | lacquered                  |
| Material               | thermoplastic              |
| Surface appearance     | velvety                    |

### Dimensions

|   |       |
|---|-------|
| Insertion depth                         | 32 mm |
| Installation depth, flush-mounted boxes | 31 mm |

### Installation, mounting

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

### Connection

|                      |                                 |
|----------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1        |
| Connection terminals | according to VDE 0620-1:2021-02 |
| -                    | with screw-in lift terminals    |

### Use

|  |                             |
|--|-----------------------------|
| Differentiation characteristic 1 - Sales | with labelling field        |
| Differentiation characteristic 2 - Sales | enhanced contact protection |
| Differentiation characteristic 3 - Sales | Screw-in lift terminals     |

---

**Safety**

---

|   |                                 |
|---|---------------------------------|
| IK protection code against mechanical impacts | 02                              |
| Protection index IP                           | IP20                            |
| Enhanced contact protection                   | according to IEC 60884-1        |
| Enhanced contact protection                   | according to VDE 0620-1:2021-02 |
| - Enhanced contact protection                 |                                 |

---

**Identification**

---

|                          |  |
|--------------------------|--|
| Main design line         | Berker Q.1/Q.3/Q.7/Q.9                         |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |

---

**Instructions**

---

|                  |  |
|------------------|--|
| Information text | Labelling field height arranged for P-touch strips 6 mm. |
|------------------|--|

---