



47506003



SCHUKO socket outlet with labelling field, Berker Q.1/Q.3/Q.7/Q.9, green velvety

Technical features

Arc	hitec	ture

Design	according to DIN 49440
Fixing mode	flush-mounting

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

green
green
green
RAL 6029 - Mint green
duroplastic
velvety

Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

Installation, mounting

to an Handan and a	and the second and a second
Installation mode	with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Use

Differentiation characteristic 1 - Sales	with labelling field
--	----------------------



Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	
Identification	
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9
Instructions	
Information text	Insert colour-coded. 1140.
	Labelling field height designed for 6 mm P-touch strips.