



41436014



## SCHUKO socket outlet with screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9, orange velvety

### Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

#### Connectivity

Type of USB port	other
------------------	-------

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Design lines special colours	orange
Colour	orange
Colour	orange
RAL colour	RAL 2003 - Pastel orange
Material	duroplastic
Surface appearance	velvety

#### Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
-	with screw-in lift terminals

#### Use

Differentiation characteristic 3 - Sales	with screw-in lift terminals
--	------------------------------

---

**Safety**

---

IK protection code against mechanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	

---

**Identification**

---

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

---

**Instructions**

---

Information text	Insert colour-coded.
------------------	----------------------

---