



6768766089



Socket outlet with earthing pin with enhanced touch protection, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety	
Technical features	
Architecture	
Fixing mode	flush-mounting
- 2pole + earth	
Connectivity	
Type of USB port	other
Main electrical features	
Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A
Cover, door	
Cover	Central cover plate
Materials	
Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	duroplastic
Surface appearance	velvety
Dimensions	
Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm
Mirror depth	14,5 mm
Installation, mounting	
Installation mode	with spreader claws
Connection	
Connection terminals	according to IEC 60884-1
- with plug-in terminals	
Use	
Differentiation characteristic 2 - Sales	with enhanced touch protection
Safety	
IK protection code against mechanical impacts	02
Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9