



6768766074

**Socket outlet with earthing pin with enhanced touch protection, Berker Q.1/Q.3/Q.7/Q.9**

Technical features

**Architecture**

Fixing mode	flush-mounting
- 2pole + earth	

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material	duroplastic
Surface appearance	velvety

**Dimensions**

Installation depth, flush-mounted boxes	31 mm
Mirror depth	14,5 mm

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
----------------------	--------------------------

**Use**

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

**Safety**

IK protection code against mechanical impacts	05
- without enhanced contact protection	

**Identification**

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.3, Berker Q.1, Berker Q.7, Berker Q.9