



6765096015



**Socket outlet with earth contact pin and monitoring LED with enhanced touch protection, Screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9, red velvety**

Technical features

**Architecture**

Fixing mode	flush-mounting
- 2pole + earth	

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Design lines special colours	red
Colour	red
Colour	red
RAL colour	RAL 3003 - Ruby red
Material	duroplastic
Surface appearance	velvety

**Dimensions**

Insertion depth	32 mm
-----------------	-------

**Installation, mounting**

Installation mode	with spreader claws
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

**Use**

Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

**Safety**

Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

**Identification**

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9