


6768776086



Socket outlet with earthing pin and hinged cover with enhanced touch protection, Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered

Technical features

Architecture

| | |
|-----------------|----------------|
| Fixing mode | flush-mounting |
| - 2pole + earth | |

Connectivity

| | |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Cover, door

| | |
|-------------------------------------|---------------------|
| Cover | Central cover plate |
| - with hinged cover that falls back | |

Materials

| | |
|------------------------|--------------------------|
| Colour of design line | anthracite |
| Colour | anthracite |
| Colour | anthracite charcoal grey |
| RAL colour | RAL 7021 - Black grey |
| Material / workmanship | lacquered |
| Material | thermoplastic |
| Surface appearance | velvety |

Dimensions

| | |
|-----------------|---------|
| Insertion depth | 31,2 mm |
| Mirror depth | 14,5 mm |

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|--------------------------|--------------------------|
| Connection terminals | according to IEC 60884-1 |
| - with plug-in terminals | |

Use

| | |
|--|--------------------------------|
| Differentiation characteristic 2 - Sales | with enhanced touch protection |
|--|--------------------------------|

Safety

| | |
|---|--------------------------|
| IK protection code against mechanical impacts | 05 |
| Enhanced contact protection | according to IEC 60884-1 |
| - Enhanced contact protection | |

Identification

| | |
|--------------------------|--|
| Main design line | Berker Q.1/Q.3/Q.7/Q.9 |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |
