



6768776084



Socket outlet with earthing pin and hinged cover with enhanced touch protection, Berker Q.1/Q.3/Q.7/Q.9

Technical features

Architecture

Fixing mode flush-mounting

- 2pole + earth

Connectivity

Type of USB port other

Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

Rated current 16 A

Cover, door

Cover Central cover plate

- with hinged cover that falls back

Materials

Colour of design line aluminium

Colour aluminium

Colour aluminium optics

RAL colour RAL 9006 - White aluminium

Material / workmanship lacquered

Material thermoplastic

Surface appearance velvety

Dimensions

Insertion depth 31,2 mm

Mirror depth 14,5 mm

Installation, mounting

Installation mode with spreader claws

Connection

Connection terminals according to IEC 60884-1

- with plug-in terminals

Use

Differentiation characteristic 2 - Sales with enhanced touch protection

Safety

IK protection code against mechanical impacts 05

Enhanced contact protection according to IEC 60884-1

- Enhanced contact protection

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9
