



85241126



IP20

## Blind time switch Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered

### Technical features

### Functions

Venetian blind movement time	2 mn
- Memory function for automatic execution of learned up and down times with position	
- Party function, no execution of automatic, radio and extension unit commands (lock-out protection)	

### Controls and indicators

- activation of the party function using buttons in up and down direction > 20 sec.

### Main electrical features

Nominal voltage	12 V
Frequency	- Hz

### Measurement

Relative humidity (without condensation)	0...65 % (without condensation)
--	---------------------------------

### Detection

- Not suitable for rain and wind sensors

### Materials

Colour of design line	anthracite
Colour	anthracite
Material / workmanship	lacquered
Material	thermoplastic

### LED control

LED	LED application module/insert compatibility display, with status LED for memory and party function, red/orange, with indicator LED for lock-out protection
-----	--

### Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

### Settings

Lamella adjusting time	(adjustable) 50 ms...2,5 s
Minimum slat adjustment time	≈ 250 ms
Delay time, adjustable	0...500 s
Lamella adjustment on button-press	< 0,4 s

### Equipment

Self-retaining for 2 min on button-press	> 0,4 s
Change-over time for change of direction	< 0,6 s

### Safety

- with dismantling protection

---

**Use conditions**

Operating temperature	-5...45 °C
- low intrinsic energy requirement	

---

**Identification**

Application, usage	Blind control
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

---

**Instructions**

- Can be switched to orientation led by extension unit.
---

---