



3315406084



VGA socket outlet Berker Q.1/Q.3/Q.7/Q.9

Technical features

Connectivity

- with straight outlet
- S-VGA compatible
- with 15pole D-subminiature jack (front)

Frequency

| | |
|-----------------------|--------------|
| Frequency range video | max. 160 MHz |
|-----------------------|--------------|

Screen

| | |
|------------|---------------------|
| Resolution | max. 1280 x 1024 px |
|------------|---------------------|

Materials

| | |
|-----------------------|----------------------------|
| Colour of design line | aluminium |
| Colour | aluminium |
| RAL colour | RAL 9006 - White aluminium |
| Material | Plastic/metal |
| Surface appearance | velvety |

Dimensions

| | |
|-----------------|-------|
| Insertion depth | 12 mm |
|-----------------|-------|

Installation, mounting

| | |
|-------------------|------------------------|
| Installation mode | without spreader claws |
|-------------------|------------------------|

Connection

| | |
|------------|--|
| Connection | with 15pole D-subminiature double jack |
|------------|--|

- with backside jack for connecting to pre-assembled VGA cable

Equipment

- with supporting ring

Identification

| | |
|--------------------------|--|
| Main design line | Berker Q.1/Q.3/Q.7/Q.9 |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |

Instructions

| | |
|------------------|--|
| Information text | <p>For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors., Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74</p> |
|------------------|--|