



20346084



**Thermostat, NO contact, with centre plate, for underfloor heating with rocker switch, external temperature sensor, Berker Q.1/Q.3/Q.7/Q.9**

Technical features

#### Functions

- with on/off switch and 2 LEDs

#### Main electrical features

Nominal voltage	230 V
Rated voltage	230 V AC
Frequency	50/60 Hz

#### Electric current

Switching current	10 A
-------------------	------

#### Materials

Colour of design line	aluminium
Colour	aluminium
Material / workmanship	lacquered
Material	Plastic/metal

#### LED control

LED	with LED for heating and LED for night lowering
-----	---

#### Installation, mounting

Installation mode	without spreader claws
-------------------	------------------------

#### Connection

Sensor cable length	4 m
Connection	with separate connection for night lowering
- with plug-in terminals	

#### Settings

Floor temperature setting range	10...50 °C
Room temperature setting range	5...30 °C

#### Equipment

Night lowering	≈ 5 K
Switching temperature difference	≈ 1 K
- setting knob with temperature range limitation	
- e.g. for valve drives closed in de-energised state	

#### Use

Differentiation characteristic 1 - Sales	with rocker switch
Differentiation characteristic 3 - Sales	external temperature sensor

**Use conditions**

---

Energy efficiency class	I (1%)
- with thermal return	

---

**Identification**

---

Application, usage	HVAC control
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

---