



85241175



IP20

### Blind button Berker K.1, anthracite matt, lacquered

#### Technical features

#### Functions

Venetian blind movement time 2 mn

- Memory function for automatic execution of learned up and down times with position
- Party function, no execution of automatic, radio and extension unit commands (lock-out protection)

#### Controls and indicators

- activation of the party function using buttons in up and down direction > 20 sec.

#### Main electrical features

Nominal voltage 12 V

Frequency - Hz

#### Measurement

Relative humidity (without condensation) 0...65 % (without condensation)

#### Detection

- Not suitable for rain and wind sensors

#### Materials

Colour of design line anthracite

Colour anthracite

Material / workmanship lacquered

Material thermoplastic

#### LED control

LED LED application module/insert compatibility display, with status LED for memory and party function, red/orange, with indicator LED for lock-out protection

#### Installation, mounting

Installation mode clamp fastening

#### Settings

Lamella adjusting time (adjustable) 50 ms...2,5 s

Minimum slat adjustment time ≈ 250 ms

Delay time, adjustable 0...500 s

Lamella adjustment on button-press < 0,4 s

#### Equipment

Self-retaining for 2 min on button-press > 0,4 s

Change-over time for change of direction < 0,6 s

#### Safety

- with dismantling protection

---

**Use conditions**

---

Operating temperature	-5...45 °C
-----------------------	------------

---

- low intrinsic energy requirement

---

**Identification**

---

Application, usage	Blind control
Main design line	Berker K.1
Secondary design line(s)	Electronics platform, Berker K.1

---

**Instructions**

---

- Can be switched to orientation led by extension unit.

---