



47287106



SCHUKO socket outlet 45° with labelling field, Berker K.1, anthracite matt, lacquered

Technical features

| A | L : L _ | |
|-----|---------|-------|
| Arc | nite | cture |

| Design | according to DIN 49440 |
|-------------|------------------------|
| Fixing mode | flush-mounting |

Main electrical features

| Nominal voltage | 250 V |
|-----------------|----------|
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| Rated current | 16 A |
|---------------|------|
|---------------|------|

Cover, door

| Cover | Central cover plate |
|-------|---------------------|
|-------|---------------------|

Materials

| Colour of design line | anthracite | | | |
|------------------------|--------------------------|--|--|--|
| Colour | anthracite | | | |
| Colour | anthracite charcoal grey | | | |
| RAL colour | RAL 7021 - Black gre | | | |
| Material / workmanship | lacquered | | | |
| Material | thermoplastic | | | |
| Surface appearance | ma | | | |
| | | | | |

Dimensions

| Insertion depth | 32 mm |
|-----------------|-------|
|-----------------|-------|

Installation, mounting

| Installation mode | with spreader claws |
|--------------------------|---------------------|
| - for diagonal insertion | |

Connection

| Connection terminals | according to IEC 60884-1 |
|--------------------------|---------------------------------|
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with plug-in terminals | |

Use

| Differentiation characteristic 1 - Sales | ith | ١la | abe | ellir | ng i | fiel | d |
|--|-----|-----|-----|-------|------|------|---|
|--|-----|-----|-----|-------|------|------|---|

Safety

| IK protection code against mecanical impacts | |
|--|------|
| Protection index IP | IP20 |
| - without enhanced contact protection | |



| Identification | |
|------------------|---|
| Main design line | Berker K.1 |
| Instructions | |
| Information text | Specially suited to combinations of several socket outlets if right angle plugs are used. 1140. |
| | Labelling field height designed for 6 mm P-touch strips. |