




41157004



**SCHUKO socket outlet with screw-in lift terminals, Berker K.5, stainless steel, metal matt finish**

Technical features

**Architecture**

Design according to DIN 49440

Fixing mode flush-mounting

**Connectivity**

Type of USB port other

**Main electrical features**

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

Rated current 16 A

**Electric current**

Rated current 16 A

**Cover, door**

Cover Central cover plate

**Materials**

Colour of design line Stainless steel

Colour stainless steel

Colour stainless steel optics

RAL colour RAL 9022 - Pearl light grey

Material / workmanship metal, matt finish

Material stainless steel

Surface appearance matt

**Dimensions**

Insertion depth 32 mm

Installation depth, flush-mounted boxes 31 mm

**Installation, mounting**

Installation mode with spreader claws

**Connection**

Connection terminals according to IEC 60884-1

Connection terminals according to VDE 0620-1:2021-02

- with screw-in lift terminals

**Use**

Differentiation characteristic 3 - Sales with screw-in lift terminals

**Safety**

---

IK protection code against mechanical impacts	07
Protection index IP	IP20
- without enhanced contact protection	

---

**Identification**

---

Main design line	Berker K.5
------------------	------------

---