



85741175



IP20

Blind time switch with display, Berker K.1, anthracite matt, lacquered

Technical features

Functions

| | |
|--|---------|
| Astronomic time shift | ± 2 h |
| Running time | 2 mn |
| Random number generator | ± 15 mn |
| Power reserve | ≈ 24 h |
| <ul style="list-style-type: none"> - reset function (to factory setting) - with keylock - Party function, no execution of automatic, radio and extension unit commands (lock-out protection) - with switchover manual/automatic mode | |

Controls and indicators

- LC display illuminated during operation
- indication of the application module/insert compatibility in the display
- LC display contrast is adjustable

Main electrical features

| | |
|-----------------|------|
| Nominal voltage | 12 V |
| Frequency | - Hz |

Measurement

| | |
|--|---------------------------------|
| Relative humidity (without condensation) | 0...65 % (without condensation) |
|--|---------------------------------|

Detection

- Not suitable for rain and wind sensors

Materials

| | |
|------------------------|---------------|
| Colour of design line | anthracite |
| Colour | anthracite |
| Material / workmanship | lacquered |
| Material | Plastic/metal |

Installation, mounting

| | |
|-------------------|-----------------|
| Installation mode | clamp fastening |
|-------------------|-----------------|

Settings

| | |
|--|--|
| Minimum slat adjustment time | ≈ 250 ms |
| Lamella adjustment on button-press | < 0,5 s |
| Time | with automatic summer-/winter time switching (can be switched off) |
| <ul style="list-style-type: none"> - astro programme for sunrise/sundown switching with city/country or co-ordinate input, individually adaptable - holiday programme for random variation of the operation times in automatic operation | |

Equipment

| | |
|---|---------|
| Number of operation times for up/down | 20 |
| Self-retaining for 2 min on button-press | > 0,5 s |
| Change-over time for change of direction | < 0,6 s |
| - 2 independent preset programme memories, individually adaptable | |

Use

| | |
|--|--------------|
| Differentiation characteristic 2 - Sales | with display |
|--|--------------|

Safety

- with dismantling protection

Use conditions

| | |
|------------------------------------|------------|
| Operating temperature | -5...45 °C |
| - low intrinsic energy requirement | |

Identification

| | |
|--------------------------|----------------------------------|
| Application, usage | Blind control |
| Main design line | Berker K.1 |
| Secondary design line(s) | Electronics platform, Berker K.1 |

Instructions

- Can be switched to orientation led by extension unit.