



6765107004



**Socket outlet with earthing pin and LED orientation light enhanced contact protection, Screw-in lift terminals, Berker K.5, stainless steel matt, lacquered**

Technical features

### Architecture

Fixing mode	flush-mounting
- 2pole + earth	

### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

### Power

Power consumption	0.25 W/0.35 VA
-------------------	----------------

### Cover, door

Cover	Central cover plate
-------	---------------------

### Detection

- integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness

### Materials

Colour of design line	stainless steel
Colour	stainless steel
Colour	stainless steel optics
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	matt

### Dimensions

Insertion depth	32 mm
-----------------	-------

### Lighting control

Switch-off brightness	≈ 4 lx
Switch-on brightness	≈ 2 lx
Light intensity (white)	0,2 cd

### LED control

LED	long service life of the LED, white LED light
-----	---

### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

### Connection

Conductor cross-section (rigid)	max. 2,5 mm <sup>2</sup>
Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

### Cable

- through-wiring possible, therefore also ideal for retrofitting

### Equipment

- additional benefit by combination of a socket outlet with an orientation light

### Use

Differentiation characteristic 2 - Sales	enhanced contact protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

### Safety

IK protection code against mechanical impacts	05
Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

### Identification

Main design line	Berker K.5
------------------	------------

### Instructions

Information text	Caution! Items with special flush-mounted insert. Centre plates with LED orientation lights are not compatible with the standard socket outlets.
------------------	--