




6765777103



**Socket outlet with earthing pin and hinged cover with enhanced touch protection, with screw-in lift terminals, Berker K.5, Aluminium, aluminium anodised**

#### Technical features

#### Architecture

Fixing mode	flush-mounting
- 2pole + earth	

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Cover, door

Cover	Central cover plate
- when opening hinged cover, it can be arrested in end position	

#### Materials

Colour of design line	Aluminium
Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material / workmanship	aluminium, anodised
Material	Aluminium
Surface appearance	matt

#### Dimensions

Insertion depth	32 mm
-----------------	-------

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

#### Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	with screw-in lift terminals

#### Safety

IK protection code against mechanical impacts	07
Enhanced contact protection	according to IEC 60884-1
- enhanced contact protection VDE 0620-1:2021-02	

#### Identification

Main design line	Berker K.5
------------------	------------