



41527104



SCHUKO socket outlet with overvoltage protection with labelling field, Screw terminals, Berker K.5, stainless steel matt, lacquered

Technical features

Architecture

| | |
|-------------|------------------------|
| Design | according to DIN 49440 |
| Fixing mode | flush-mounting |

Controls and indicators

- with acoustic fault signal

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Voltage

| | |
|------------------------|---|
| Overvoltage protection | according to EN 61643 and VDE 0675-6-11 |
|------------------------|---|

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

Materials

| | |
|------------------------|-----------------------------|
| Colour of design line | stainless steel |
| Colour | stainless steel |
| Colour | stainless steel optics |
| RAL colour | RAL 9022 - Pearl light grey |
| Material / workmanship | lacquered |
| Material | Plastic/metal |
| Surface appearance | matt |

Dimensions

| | |
|-----------------|-------|
| Insertion depth | 32 mm |
|-----------------|-------|

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|------------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with screw terminals | |

Equipment

- with indicator LED for On/Error

Use

| | |
|--|----------------------|
| Differentiation characteristic 1 - Sales | with labelling field |
| Differentiation characteristic 3 - Sales | Screw terminals |

Safety

| | |
|---|------|
| IK protection code against mechanical impacts | 07 |
| Protection index IP | IP20 |
| - without enhanced contact protection | |

Identification

| | |
|------------------|------------|
| Main design line | Berker K.5 |
|------------------|------------|

Instructions

| | |
|------------------|--|
| Information text | Labelling field height arranged for P-touch strips 6 mm. |
|------------------|--|
