



47399004



**SCHUKO socket outlet with labelling field, Berker Arsys, stainless steel matt, lacquered**

Technical features

**Architecture**

|             |                        |
|-------------|------------------------|
| Design      | according to DIN 49440 |
| Fixing mode | flush-mounting         |

**Connectivity**

|                  |       |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

**Main electrical features**

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

**Electric current**

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

**Cover, door**

|       |                     |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

**Materials**

|                        |                             |
|------------------------|-----------------------------|
| Colour of design line  | stainless steel             |
| Colour                 | stainless steel             |
| Colour                 | stainless steel optics      |
| RAL colour             | RAL 9022 - Pearl light grey |
| Material / workmanship | lacquered                   |
| Material               | duroplastic                 |
| Surface appearance     | matt                        |

**Dimensions**

|                                         |       |
|-----------------------------------------|-------|
| Insertion depth                         | 32 mm |
| Installation depth, flush-mounted boxes | 32 mm |

**Installation, mounting**

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

**Connection**

|                          |                                 |
|--------------------------|---------------------------------|
| Connection terminals     | according to IEC 60884-1        |
| Connection terminals     | according to VDE 0620-1:2021-02 |
| - with plug-in terminals |                                 |

**Use**

|                                          |                      |
|------------------------------------------|----------------------|
| Differentiation characteristic 1 - Sales | with labelling field |
|------------------------------------------|----------------------|

---

**Safety**

---

|                                               |      |
|-----------------------------------------------|------|
| IK protection code against mechanical impacts | 02   |
| Protection index IP                           | IP20 |
| - without enhanced contact protection         |      |

---

**Identification**

---

|                  |              |
|------------------|--------------|
| Main design line | Berker Arsys |
|------------------|--------------|

---

**Instructions**

---

|                  |                                                          |
|------------------|----------------------------------------------------------|
| Information text | Labelling field height arranged for P-touch strips 6 mm. |
|------------------|----------------------------------------------------------|

---