





Double SCHUKO socket outlet with frame Berker Arsys, brown glossy

Technical features

| rcl | | |
|-----|--|--|
| | | |
| | | |
| | | |

| Design | according to DIN 49440 |
|-------------|------------------------|
| Fixing mode | flush-mounting |

Main electrical features

| Nominal voltage | 250 V |
|-----------------|----------|
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| Rated current | 16 A |
|---------------|------|
|---------------|------|

Cover, door

| Cover | Central cover plate |
|-------|---------------------|
|-------|---------------------|

Materials

| brown |
|----------------------|
| brown |
| brown |
| RAL 8011 - Nut brown |
| duroplastic |
| glossy |
| |

Dimensions

| Insertion depth | 32 mm |
|-------------------|-------|
| Assembling height | 22 mm |

Installation, mounting

| For installation in 1gang wall boxes | according to DIN 49073-1 |
|--------------------------------------|--------------------------|
| Installation mode | with spreader claws |

Connection

| Connection terminals | according to IEC 60884-1 |
|--------------------------|---------------------------------|
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with plug-in terminals | |

Safety

| IK protection code against mecanical impacts | 02 |
|----------------------------------------------|------|
| Protection index IP | IP20 |
| - without enhanced contact protection | |

Identification

| Main design line | Parker Arova |
|------------------|--------------|
| Main design line | Berker Arsvs |