

47290001 I

____<u>2</u>

Double SCHUKO socket outlet with frame enhanced contact	protection. Berker Arsys. brown glossy

Technical features

Design	according to DIN 49440
Fixing mode	flush-mounting
Main electrical features	
Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A
Electric current	
Rated current	16 4
Cover, door	
Cover	Central cover plate
Materials	
Colour of design line	brown
Colour	browr
Colour	brown
RAL colour	RAL 8011 - Nut brown
Material	duroplastic
Surface appearance	glossy
Dimensions	
Insertion depth	32 mm
Assembling height	22 mm
Installation, mounting	
For installation in 1gang wall boxes	according to DIN 49073-
Installation mode	with spreader claws
Connection	
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	
Use	
Differentiation characteristic 2 - Sales	enhanced contact protection



Safety

K protection code against mecanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
Enhanced contact protection	

Identification

Main design line	Berker Arsys
------------------	--------------