



41100077







SCHUKO socket outlet with control LED and "ZSV" imprint with labelling field, enhanced contact protection, Screw-in lift terminals, Berker Arsys, orange glossy

Technical features

		٠.		
Λr	n	IITC	ctu	ırα
AI.	u	ıııe		ai C

Design	according to DIN 49440
Fixing mode	flush-mounting
Technical version	Imprint "ZSV"

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Design lines special colours	orange
Colour	orange
Colour	orange
RAL colour	RAL 2003 - Pastel orange
Material	thermoplastic
Surface appearance	glossy

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to VDE 0620-1:2021-02
- with screw-in lift terminals	

Use

with labelling field	Differentiation characteristic 1 - Sales	
enhanced contact protection	Differentiation characteristic 2 - Sales	
Screw-in lift terminals	Differentiation characteristic 3 - Sales	

Standards

Execution SV, ZSV	according to VDE 0100-710
-------------------	---------------------------



Safety

IK protection code against mecanical impacts	05
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	
Identification	
Main design line	Berker Arsys
Instructions	
Information text	Labelling field height arranged for P-touch strips 6 mm., Insert colour-coded.