



47340002



#### SCHUKO socket outlet with enhanced touch protection, Berker Arsys, gold matt, aluminium anodised

**Technical features** 

AICHILECTULE	Arc	hite	cture
--------------	-----	------	-------

Design	according to DIN 49440
Fixing mode	flush-mounting

# Connectivity

Type of USB port	other
Type of GGD port	Other

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### **Electric current**

Rated current	16 A

#### Cover, door

Cover	Central cover plate

#### Materials

gold
gold
old optics
en yellow
anodised
luminium
matt

#### **Dimensions**

Insertion depth	32 mm
Installation denth flush-mounted hoves	32 mm

# Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

## Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

### Use



# Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	
Identification	
Main design line	Berker Arsys