



3315407003



### VGA socket outlet Berker K.5, aluminium, matt, lacquered

**Technical features** 

### Connectivity

- with straight outlet
- S-VGA compatible
- with 15pole D-subminiature jack (front)

Frequency
-----------

Frequency range video max. 160 MHz

#### Screen

Resolution max. 1280 x 1024 px

### Materials

Colour of design linealuminiumColouraluminiumRAL colourRAL 9006 - White aluminiumMaterial / workmanshiplacqueredMaterialPlastic/metalSurface appearancematt

### **Dimensions**

Insertion depth 12 mm

# Installation, mounting

Installation mode without spreader claws, for screw fastening

## Connection

Connection with 15pole D-subminiature double jack

- with backside jack for connecting to pre-assembled VGA cable

# **Equipment**

- with supporting ring

## Identification

Application, usage Communication technology
Main design line Berker K.5

# Instructions

Information text

For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors., Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or

9062-74