



6765091909



**Socket outlet with earth contact pin and monitoring LED with enhanced touch protection, Screw-in lift terminals, Berker S.1/B.3/B.7, polar white matt**

#### Technical features

#### Architecture

Fixing mode	flush-mounting
- 2pole + earth	

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

#### Dimensions

Insertion depth	32 mm
-----------------	-------

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

#### Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

#### Safety

Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

#### Identification

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7