



47436012



SCHUKO socket outlet Berker Q.1/Q.3/Q.7/Q.9, red velvety

Technical features

AICHILECTULE	Arc	hite	cture
--------------	-----	------	-------

Design	according to DIN 49440
Fixing mode	flush-mounting

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

red
red
red
- Ruby red
uroplastic
velvety

Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

Installation, mounting

to an Handan are also	and the second and a second
Installation mode	with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20

- without enhanced contact protection



Ide			

Nactor destant for	Parker 0 1 /0 0 /0 7 /0 0
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9
Instructions	
Information text	Insert colour-coded.