



16408984



Relay switch with centre plate for hotel card Berker S.1/B.3/B.7, aluminium matt

Technical features

Architecture

Fixing mode flush-mounting

Configuration

- 1pole

Main electrical features

Nominal voltage 230 V

Rated voltage 230 V AC

Frequency 50/60 Hz

Electric current

Inductive load at $\cos \varphi = 0.6$ max. 6 A

Switching current 10 A /230 V AC1

Power

Conventional transformers 1500 VA

Electronic transformers 1500 W

Power consumption < 0.2 W

Materials

Colour of design line aluminium

Colour aluminium

Colour aluminium optics

RAL colour RAL 9006 - White aluminium

Material Plastic/metal

Surface appearance matt

Dimensions

Depth 57,3 mm

Insertion depth 32 mm

Card width max. 55 mm

Card thickness 0,8...1,2 mm

Height 71 mm

Width 71 mm

Fluorescent bulbs control

Compact fluorescent lamps 500 W

Fluorescent lamps in duo circuit 1500 W

LED control

LED illuminated with blue LED if hotel card is not inserted

Incandescent bulbs control

230 V incandescent lamps and halogen lamps	1500 W
--	--------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Screw terminals (max.)	2 x 2,5 mm ²
------------------------	-------------------------

- with screw-in lift terminals

Settings

Delay time incrementally adjustable	0, 15, 30, 60 s
-------------------------------------	-----------------

- with potentiometer for incremental adjustment of delay time

Equipment

- for illumination
- with potential-free contact

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-5...50 °C
Storage/transport temperature	-25...70 °C (storage at > 45°C reduces the service life)

Identification

Application, usage	Light control
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7
