



Combination SCHUKO socket outlet 2gang with frame Berker Q.1, anthracite velvety, lacquered

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	anthracite
Colour	anthracite
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black grey
Material / workmanship	lacquered
Material	duroplastic
Surface appearance	velvety

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	without spreader claws, for screw fastening
-------------------	---

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Cable

- 2 x 1 gang, wired-through	
-----------------------------	--

Safety

IK protection code against mechanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	

47206086



Identification

Main design line	Berker Q.1
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9
