



41681909



Socket outlet with earthing contact USA/CANADA NEMA 5-20 R with screw terminals, Berker S.1/B.3/B.7, polar white matt, lacquered

**Technical features** 

Arc	hi	te	ct	ur	e

Fixing mode	flush-mounting
- 2pole + earth	

#### Main electrical features

Nominal voltage	125 V
Rated voltage	125 V AC
Frequency	50/60 Hz
Rated current	20 A

#### Cover, door

Central cover plate

#### Materials

polar white	Colour of design line
polarwhite	Colour
white	Colour
RAL 9010 - Pure white	RAL colour
lacquered	Material / workmanship
thermoplastic	Material
matt	Surface appearance

## **Dimensions**

Insertion depth	19 mm
-----------------	-------

#### Installation, mounting

Installation mode w	vithout spreader claws, for screw fastening
---------------------	---

#### Connection

Conductor cross-section (rigid)	max. 2 x 4 mm²
- with screw terminals	

#### Use

Differentiation characteristic 3 - Sales wi	ith screw terminals
---	---------------------

## Standards

Standard	NEMA 5-20 R
----------	-------------

# Safety

IK protection code against mecanical impacts	05
- without enhanced contact protection	



## Identification

Made design the	D 0 1 /D 0 /D 7
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7
Instructions	
Information text	Not UL-certified.