




41666089



Socket outlet with earthing contact USA/CANADA NEMA 5-15 R with screw terminals, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety

Technical features

Architecture

Fixing mode	flush-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	125 V
Rated voltage	125 V AC
Frequency	50/60 Hz
Rated current	15 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	velvety

Dimensions

Insertion depth	19 mm
-----------------	-------

Installation, mounting

Installation mode	without spreader claws, for screw fastening
-------------------	---

Connection

- with screw terminals	
------------------------	--

Use

Differentiation characteristic 3 - Sales	with screw terminals
--	----------------------

Standards

Standard	NEMA 5-15 R
----------	-------------

Safety

IK protection code against mechanical impacts	05
- without enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

Instructions

Information text

Not UL-certified.