



6768776089



Socket outlet with earthing pin and hinged cover with enhanced touch protection, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety

Technical features

Architecture

Fixing mode	flush-mounting
- 2pole + earth	

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Cover, door

Cover	Central cover plate
- with hinged cover that falls back	

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	velvety

Dimensions

Insertion depth	31,2 mm
Mirror depth	14,5 mm

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
- with plug-in terminals	

Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

Safety

IK protection code against mechanical impacts	05
Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9