



**Flush-mounted housing for 7" Touch Panel, flush-to-wall KNX, anthracite, lacquered**

Technical features

**Architecture**

Fixing mode flush-mounting

**Functions**

Touch function no  
- with Push-to-open mechanism for comfortable mounting

**Controls and indicators**

- depending on the software visualisation one and two surface operation, stepless configuration based on sliding and page scrolling by swiping are supported

**Connectivity**

Connection RJ45 cable in scope of delivery  
- with USB/Mini USB type A adapter cable  
- with RJ45 connector kit from connector and patch cable

**Measurement**

Relative humidity (without condensation) 10...90 %

**Screen**

Display no

**Materials**

RAL colour RAL 7016 - Anthracite grey  
Material Steel

**Dimensions**

Cavity wall opening (W x H x D) 269 x 186 x 74 mm

**Installation, mounting**

Installation mode for flush-mounted and hollow-wall mounting, for vertical and horizontal mounting

**Scope of delivery**

- Microphone and loudspeaker with echo suppression

**Equipment**

Interface type other  
Text field no  
- Display illumination can be switched on automatically using brightness sensor  
- silent, long-lasting convection cooling without fan

**Safety**

Protection index IP IP20  
- with cleaning cover

75900207

IP20

**Use conditions**

---

Storage/transport temperature	-20...60 °C
-------------------------------	-------------

---

**Identification**

---

Composition	other
Main design line	KNX

---