



Flush-mounted housing for 16" Touch Panel, flush-to-wall KNX, anthracite, lacquered

Technical features

Architecture

Fixing mode flush-mounting

Functions

Touch function no

- with Push-to-open mechanism for comfortable mounting

Controls and indicators

- depending on the software visualisation one and two surface operation, stepless configuration based on sliding and page scrolling by swiping are supported

Connectivity

Connection RJ45 cable in scope of delivery

- with USB/Mini USB type A adapter cable
- with RJ45 connector kit from connector and patch cable

Measurement

Relative humidity (without condensation) 10...90 %

Screen

Display no

Materials

RAL colour RAL 7016 - Anthracite grey

Material Steel

Dimensions

Cavity wall opening (W x H x D) 387 x 242 x 74 mm

Installation, mounting

Installation mode for flush-mounted and hollow-wall mounting, for vertical and horizontal mounting

Scope of delivery

- Microphone and loudspeaker with echo suppression

Equipment

Interface type other

Text field no

- Display illumination can be switched on automatically using brightness sensor
- silent, long-lasting convection cooling without fan

Safety

Protection index IP IP20

- with cleaning cover

75900216

IP20

Use conditions

Storage/transport temperature	-20...60 °C
-------------------------------	-------------

Identification

Composition	other
Main design line	KNX
