



75143855



IP20

## Touch sensor 3gang comfort with integral bus coupling unit, KNX - Berker R.3, glass black

### Technical features

#### Architecture

Fixing mode flush-mounting

#### Functions

With room temperature controller yes

- for switch, push-button, dimmer and shutter functions
- Blocking function for sensor surface e.g. for cleaning the glass surface

#### Compatibility

- extension unit for light scene push-button

#### Controls and indicators

With LED indication yes

- operation by gently touching the sensor surfaces on the white LED

#### Power

Current consumption 12,5 mA

#### Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

#### Screen

With display no

#### Materials

Colour of design line glass black

Colour black

RAL colour RAL 9005 - Jet black

Material glass

Surface appearance glossy

Type of surface treatment Tampography

#### Dimensions

Depth 23 mm

Height 152 mm

Width 81 mm

#### LED control

LED with blue operation LED and 6 white status LEDs

#### Installation, mounting

Installation mode for vertical mounting

### Connection

- with integral bus coupling unit
- bus connection via connecting terminal

### Scope of delivery

Bus connection included yes

### Accessories included

Inscribable, with labelling field no

- for additional products to complement the installation in matching colours/materials, refer to the Design platform R.1/R.3
- for suitable frames in the same "style" for additional applications, see the Design line R.x

### Equipment

Number of actuation points 6

With anti-theft/dismantling protection yes

Type of configuration Laserdruck

### Use

Differentiation characteristic 3 - Sales with integral bus coupling unit

### Safety

Protection index IP IP20

Halogen free no

### Use conditions

Operating temperature -5...45 °C

- temperature measurement via internal temperature sensor or external communication object
- integrated temperature sensor for operation as controller extension unit
- additional connection for external temperature sensor

### Identification

Application, usage KNX - operating systems

Main design line KNX - Berker R.3

Secondary design line(s) KNX, Berker R.3