



75314023



**IP20**

## Roller shutter actuator 4gang RMD 230 V AC KNX, lighth grey

### Technical features

#### Architecture

Bus system	KNX
Number of blinds/shutters outputs	4
Fixing mode	REG
Technical version	4gang

#### Functions

Bus module detachable	no
Operating mode	operating mode only roller shutters
<ul style="list-style-type: none"> <li>- suitable to switch different external conductors</li> <li>- with sun shade function</li> <li>- with safety functions e.g. for wind, rain, alarm</li> <li>- with positioning function for roller shutter position</li> </ul>	

#### Controls and indicators

Indicator lamp	yes
<ul style="list-style-type: none"> <li>- manual operation per channel using button (single-area operation)</li> <li>- Manual operation can be activated via selection switch, thereby deactivation of the KNX function</li> <li>- for activation of an AC drive per actuator channel</li> <li>- status LED integrated in the manual operation button</li> <li>- 4 manual operation buttons for up/down per channel/device</li> <li>- with illuminated programming button</li> </ul>	

#### Connectivity

Bus system radio frequent	no
Bus system LON	no
Bus system Powernet	no

#### Main electrical features

Type of supply voltage	AC
Frequency	50/60 Hz
Rated current	6 A

#### Voltage

Operating voltage over bus	21...32 V DC
System supply voltage	30V DC via bus

#### Electric current

Bus current consumption (data transfer)	5,2 mA
Bus current consumption (idle)	5 mA
Maximum switching current	6 A
Switching current at $\cos \varphi = 0.6$	max. 6 A

#### Power

Total power loss under IN	2 W
---------------------------	-----

### Materials

Colour	light grey
RAL colour	RAL 7035 - Light grey

### Dimensions

Depth	65 mm
Width of rail mounted device (RMD)	4 modules
Height	90 mm
Width	70 mm

### LED control

LED	Status LED integrated in manual operation button
-----	--

### Connection

Connection cross-sect. flexible conductor	0,75 / 2,5mm <sup>2</sup>
Connection cross-sect. rigid cable	0,75 / 2.5mm <sup>2</sup>
Conductor cross-section (flexible)	0,75...2,5 mm <sup>2</sup>
Conductor cross-section (flexible), without wire end sleeve	0,75...2,5 mm <sup>2</sup>
Conductor cross-section (rigid)	0,75...2,5 mm <sup>2</sup>
Type of connection	quick connect
<ul style="list-style-type: none"> <li>- with integral bus coupling unit</li> <li>- with QuickConnect plug-in terminals</li> <li>- bus connection via connecting terminal</li> </ul>	

### Settings

Supported configuration modes	system
- switching time on change of direction adjustable	

### Scope of delivery

Bus connection included	yes
-------------------------	-----

### Equipment

Modular expandability	no
With slide for manual switch	yes

### Safety

Protection index IP	IP20
Halogen free	no

### Use conditions

Operating temperature	-5...45 °C
Storage/transport temperature	-20...70 °C

### Identification

Main design line	KNX
------------------	-----