



75261189



## KNX controller 1.1 m KNX - Berker S.1/B.3/B.7, polar white matt

Technical features

### Functions

- parameter defineable lock function

### Compatibility

- also suitable as extension unit

### Controls and indicators

Number of switching segments 72

### Measurement

Detection field, semi-oval shaped  $\approx 10 \times 12 \text{ m}$

### Reach distance

Range, frontal  $\approx 10 \text{ m}$

Range, side each  $\approx 6 \text{ m}$

### Cover, door

Cover with cover to limit detection angle to  $90^\circ$

### Detection

Number of detection levels 2

Detection angle  $180^\circ$

Sensor type detector of movement

### Materials

Colour of design line polar white

RAL colour RAL 9010 - Pure white

Material thermoplastic

Surface appearance matt

### Dimensions

Dimensions assembling height 23,5 mm

Nominal mounting height 1,1 m

### Lighting control

Response brightness, configurable 1...1000 lx / daytime operation

### Connection

- for bus coupling unit flush-mounted

### Settings

Supported configuration modes	system
Response sensitivity, settable	20...100 %
Delay time	≈ 10 s
Additional delay time programmable	130...152 ms
- with potentiometer for fine adjustment of the response sensitivity	

### Equipment

Product type:	product type: movement
---------------	------------------------

### Safety

Halogen free	no
--------------	----

### Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

### Identification

Application, usage	KNX - sensors
Product family	product family: physical sensors
Main design line	KNX - Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Motion detector, KNX, Berker B.7

### Instructions

Information text	Continuous direct sunlight penetrating the upward-pointing detection plane can result in failure of the motion detector. Only suitable for indoor areas!
------------------	---