



75040004



## KNX data interface USB flush-mounted KNX, black

### Technical features

#### Architecture

Fixing mode flush-mounting

#### Compatibility

Compatibility compatible with USB 1.1/2.0 transmission protocols

System requirements: system requirements: Windows 2000 or later

#### Connectivity

Bus system radio frequent no

Bus system LON no

Bus system Powernet no

- with B-type USB socket for data traffic (voltage supply via PC)

#### Voltage

Operating voltage over bus 21...32 V DC

#### Storage

Data transmission rate max. 9,6 kBd

#### Materials

Colour independent of design lines black

Colour black

RAL colour RAL 9005 - Jet black

Material Plastic/metal

Surface appearance matt

#### Installation, mounting

Installation mode without spreader claws

#### Cable

USB cable length max. 5 m

#### Settings

Supported configuration modes system

- programmable from ETS3, V1.0

- For addressing, programming and diagnosis of KNX components

#### Equipment

Interface type USB

Product type: product type: USB

#### Software

Update with flash-controller technology

---

**Safety**

---

Protection index IP	IP20
Halogen free	no

---

**Use conditions**

---

Operating temperature	-5...45 °C
-----------------------	------------

---

**Identification**

---

Application, usage	KNX - system units
Product family	product family: communication
Main design line	KNX

---